

# DYNAPAC

Part of the Atlas Copco Group

## LP6500 Duplex rollers



### Technical data

	LP6500 (Electrical)
<b>Dimensions</b>	
Drum width	26 in
Width	28 in
Height	41.14 in
Length	8,248.03 ft
<b>Masses</b>	
Net mass	1,495 lbs
Operating mass (CE)	1,579 lbs
<b>Propulsion</b>	
Theor. gradeability	35 %
<b>Compaction</b>	
Static linear load	31 lbs/ in
Speed forward	60 m/ min
Speed reverse	38 m/ min
Vibration frequency	0 vpm
Nominal amplitude	0.018 in
Centrifugal force	4,700 lb
<b>Engine</b>	
Manufacturer	Hatz
Type	1D50S
Fuel	Diesel
Rated power	6.80 kW
Rated power @	2,600 rpm
Rated power (rating standard)	SAE J1995
Fuel consumption / h	1.35 l
Fuel tank capacity	1 gal
<b>Hydraulic system</b>	
Driving	Fully hydraulic
<b>Sprinkler system</b>	
Tank capacity	71 l
Type of sprinkling	Gravity
<b>Sound and vibration values</b>	
Guaranteed sound power level, $L_{wa}$	107 dB(A)
Hand and arm vibrations (EN500-4), standard handle	4.0 m/ s <sup>2</sup>
Sound pressure level at the operator's ear (EN 500-4), $L_{pA}$	90 dB(A)
<b>Specifications</b>	
Frequency	61 Hz
Operations and Maintenance Manual	ILP6500-2EN

#### Dynapac USA

3700 East 68th Avenue, Commerce City, CO 80022 Phone: 800-732-6762 Fax: 303-288-8828

Find your local dealer at [www.dynapac.us](http://www.dynapac.us)

We reserve the right to change specifications without notice. Photos and illustrations do not always show standard versions of machines.  
The above information is a general description only, all informations are supplied without liability.